


LAMINATED METAL SHEETS

TPO

PVC

Description

Panel consisting of steel sheet 0,6 mm thickness (EN 10346), with top side pre-bonded to a 0,6 mm thickness TPO or PVC-P membrane. The bottom side is protected with a special anti-corrosion treatment.



Fields of application

Exposed finishing profiles of waterproofing membrane (vertical flashings, closings). The panel is ready to be cut and bent. The different profiles thus obtained provide aesthetic continuity with direct bonding by thermowelding between the membrane used for the current part of the waterproofing and the finishing line (fixing profiles, flashings etc.)

Packaging

TPO laminated version: 1 x 2 m: 40 sheets (80 m²) per pallet (460 kg/pallet)
 PVC-P laminated version: 1 x 2 m: 40 sheets (100 m²) per pallet (460 kg/pallet)

Application

- The panels must be fastened mechanically every 200 mm.
- The resistance to extraction of the fastener is 120 kg min.
- See Imper Italia srl specifications and instructions.

TECHNICAL FEATURES

Features	U.M.	Values	
		TPO	PVC-P
Width	m	1	1
Length	m	2	2
Thickness	mm	1,2	1,2
Weight	kg/m ²	6	5,25
Colour		Grey	Grey
Resistance to acid and alkaline solutions (coating film in Sintofoil ST or PVC-P - 28 d at 23 °C/DIN 16726)	%	Pass the test	Pass the test

Rev. 03 (09-20)

Considerando le diverse situazioni d'impiego dei prodotti e l'intervento di fattori da noi non dipendenti (supporti, condizioni di esercizio, in osservanza delle prescrizioni, ecc.), non è possibile alla IMPER ITALIA srl assumere responsabilità in merito ai risultati ottenuti. Il progresso unito alla costante ricerca dei massimi livelli prestazionali possono apportare - nel tempo - modificazioni alle informazioni contenute in questo stampato, senza che la IMPER ITALIA srl debba darne preavviso a tutti gli interessati.

