



IMPER FLANGE

TPO

PVC

Description

Inspection, testing and injection flange for partitioned and VACUUM synthetic waterproofing systems.



Fields of application

Inspection, testing and injection element of injectable hydro-reactive resins in partitioned synthetic waterproofing systems for tunnels and underground structures with membranes in PCV-P Series EUROFLEX/ECOFLEX and SINTOFOIL (TPO/FPA).

Application

IMPER FLANGE will be applied to the membrane in PVC-P or TPO by means of manual hot melting. The system consists of accessories such as quick coupling fittings and injection pipes. The installation must be carried out by qualified installers and approved by IMPER ITALIA srl.

TECHNICAL FEATURES

Dimensions	U.M.	Values
d 1	mm	10
d 3	mm	28
d 4	mm	182
h	mm	29
h 1	mm	32

Rev. 00 (11-15)

As IMPER ITALIA srl has no control over how or where its products are supplied (e.g., over substrates, service conditions, or compliance with instructions), the company cannot accept any liability arising from the use of its product or the results obtained. IMPER ITALIA srl pursues a policy of continuous product improvement. As a result, the company reserves the right to make any necessary changes to the information contained in this publication at any time and without notice.

ISO 9001
ISO 14001
OHSAS 18001
BUREAU VERITAS
Certification



Imper Italia srl Via Volta, 8 · 10071
Frazione Mappano · Borgaro (TO) Italy
Tel (+39) 011 222.54.99 · Fax (+39) 011 222.54.80
export@imper.it · www.imper.it