



IMPER ITALIA SRL

Revision nr. 1

Dated 14/11/2024

First compilation

Printed on 03/12/2024

Page n. 1/19

FLASHING DETAILS

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

FLASHING DETAILS

UFI :

Q8U2-80QK-1004-P6UA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

Bituminous elastomeric sheath

Identified Uses	Industrial	Professional	Consumer
Consume	-	-	✓
Professional	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name

IMPER ITALIA SRL srl

Full address

Via Rita Atria, 9

District and Country

10079 Mappano (TO) - Italy

Tel. +39 011 2225 499

e-mail address of the competent person

responsible for the Safety Data Sheet

safety@imper.it

1.4. Emergency telephone number

For urgent inquiries refer to

CAVp “

Osp. Pediatrico Bambino Gesù”

- Roma Tel. +39 06 68593726

Az. Osp. Univ. Foggia Tel. +39 0881 732326

Az. Osp. "A. Cardarelli" - Napoli Tel. +39 081 7472870

CAV Policlinico "Umberto I" - Roma Tel. +39 06 49978000

CAV Policlinico "A. Gemelli" - Roma Tel. +39 06 3054343

Az. Osp. "Careggi" U.O. Tossicologia Medica - Firenze Tel. +39 055 7947819

CAV Centro Nazionale di Informazione Tossicologica - Pavia Tel. +39 0382 24444

Osp. Niguarda Ca' Granda - Milano Tel. +39 02 66101029

Azienda Ospedaliera Papa Giovanni XXII –

Bergamo Tel. +39 800 883300

Azienda Ospedaliera Universitaria Integrata Verona Tel. +39 800 011858

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication:

--

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

EUH208 Contains: REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1), 1,2-BENZISOTHIAZOLIN-3-ONE
May produce an allergic reaction.

Precautionary statements:

P103 Read label before use.

P101 If medical advice is needed, have product container or label at hand.

Contains: Free crystalline silica (Fine fraction)
VOC (Directive 2004/42/EC):

Exterior walls of mineral substrate.

VOC given in g/litre of product in a ready-to-use condition : 0,01

Limit value: 40,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
QUARTZ		
INDEX -	$30 \leq x < 50$	Substance with a community workplace exposure limit.
EC 238-878-4		

	IMPER ITALIA SRL	Revision nr. 1 Dated 14/11/2024 First compilation
	FLASHING DETAILS	Printed on 03/12/2024 Page n. 3/19

CAS 14808-60-7 REACH Reg. 01-2120770509-45-XXXX Free crystalline silica (Fine fraction) INDEX -	1 ≤ x < 5	STOT RE 1 H372
EC 238-878-4 CAS 14808-60-7 REACH Reg. 01-2120770509-45-XXXX TALC INDEX -	1 ≤ x < 5	
EC 238-877-9 CAS 14807-96-6 REACH Reg. 01-2120140278-58-XXXX 1,2-BENZISOTHIAZOLIN-3-ONE INDEX 613-088-00-6	0 < x < 0,05	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1 Skin Sens. 1A H317: ≥ 0,05%
EC 220-120-9 CAS 2634-33-5 REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) INDEX 613-167-00-5	0 < x < 0,0015	LD50 Oral: 450 mg/kg, LC50 Inhalation mists/powders: 0,21 mg//4h
EC 611-341-5 CAS 55965-84-9 REACH Reg. 01-2120764691-48-XXXX		Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071, Classification note according to Annex VI to the CLP Regulation: B Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06% - < 0,6%, Skin Sens. 1A H317: ≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06% - < 0,6% ATE Oral: 100 mg/kg, LD50 Dermal: 87,12 mg/kg, LC50 Inhalation mists/powders: 0,171 mg//4h

The full wording of hazard (H) phrases is given in section 16 of the sheet.

QUARTZ

* The product contains quartz (respirable fraction) classified as STOT RE1. Since the product is sold in liquid form, it does not present risks of inhaling dust, therefore, this classification is not applicable. The danger in case of aspiration occurs when the product is in a dry state and is, for example, sanded.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.
In case of doubt or in the presence of symptoms contact a doctor and show him this document.
In case of more severe symptoms, ask for immediate medical aid.
EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.
SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.
INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.
INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.



FLASHING DETAILS

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

	IMPER ITALIA SRL	Revision nr. 1
	FLASHING DETAILS	Dated 14/11/2024 First compilation Printed on 03/12/2024 Page n. 5/19

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

AUS	Österreich	Gesamte Rechtsvorschrift für Grenzwerteverordnung 2021 , Fassung vom 14.05.2023
BEL	Belgique	Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 21.12.2022, 14]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξινογόνους παράγοντες κατά την εργασία``»
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
IRL	Éire	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-

		IMPER ITALIA SRL	Revision nr. 1		
		FLASHING DETAILS	Dated 14/11/2024 First compilation Printed on 03/12/2024 Page n. 6/19		
LUX	Luxembourg	2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019) Règlement grand-ducal du 24 janvier 2020 modifiant le règlement grand-ducal du 14 novembre 2016 concernant la protection des salariés contre les risques liés à l'exposition à des agents cancérogènes ou mutagènes au travail			
LTU	Lietuva	Jsakymas dėl lietuvs higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo			
MLT	Malta	PROTECTION OF THE HEALTH AND SAFETY OF WORKERS FROM THE RISKS RELATED TO CHEMICAL AGENTS AT WORK REGULATIONS (S.L.424.24). PROTECTION OF WORKERS FROM THE RISKS RELATED TO EXPOSURE TO CARCINOGENS OR MUTAGENS AT WORK REGULATIONS (S.L.424.22)			
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255			
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit			
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos			
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy			
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006			
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)			
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a doplňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov			
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)			
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)			
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.			
	TLV-ACGIH	ACGIH 2023			
TALC					
Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm
MAK	AUS	2			RESP
VLEP	BEL		2		
MAK	CHE	2			RESP
VME/VLE	CHE	2			RESP
VLA	ESP	2			RESP
HTP	FIN	0,5			
HTP	FIN	2			INHAL
HTP	FIN	1			RESP
TLV	GRC		10		
GVI/KGVI	HRV	1			RESP
OELV	IRL	10			INHAL
OELV	IRL	0,8			RESP
TLV	NOR	2			
TGG	NLD	0,25			RESP
NDS/NDSch	POL	4			INHAL
NDS/NDSch	POL	1			RESP
TLV	ROU	2			

FLASHING DETAILS

NGV/KGV	SWE	2	Totaldamm
NGV/KGV	SWE	1	RESP
MV	SVN	2	RESP
WEL	GBR	1	RESP
TLV-ACGIH		2	RESP

Predicted no-effect concentration - PNEC

Normal value in fresh water	91,8	mg/l
Normal value in marine water	0,918	mg/l
Normal value for fresh water sediment	0,627	mg/kg/d
Normal value for marine water sediment	0,0627	mg/kg/d
Normal value for marine water, intermittent release	72	mg/l
Normal value for fresh water, intermittent release	0,72	mg/l
Normal value for the terrestrial compartment	70,6	mg/kg/d
Normal value for the atmosphere	10	mg/m3

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		160 mg/kg bw/d		1 mg/kg bw/d				
Inhalation		1,08 mg/m3		0,771 mg/m3		2,16 mg/m3		0,434 mg/m3
Skin				0,0446 mg/kg bw/d		4,54 mg/kg bw/d		0,375 mg/kg bw/d

1,2-BENZISOTHIAZOLIN-3-ONE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00403	mg/l
Normal value in marine water	0,000403	mg/l
Normal value for fresh water sediment	0,0499	mg/kg/d
Normal value for marine water sediment	0,00499	mg/kg/d
Normal value for water, intermittent release	0,0011	mg/l
Normal value of STP microorganisms	1,03	mg/l
Normal value for the terrestrial compartment	3	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				0,345 mg/m3				6,81 mg/m3
Skin				0,345 mg/kg bw/d				0,966 mg/kg bw/d

QUARTZ

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	0,05				RESP
VLEP	BEL	0,025				
TLV	DNK	0,3				

		IMPER ITALIA SRL		Revision nr. 1	
		FLASHING DETAILS		Dated 14/11/2024	
				First compilation	
				Printed on 03/12/2024	
				Page n. 8/19	
VLA	ESP	0,05		RESP	
TLV	EST	0,1			
VLEP	FRA	0,1		RESP	
GVI/KGVI	HRV	0,1			
VLEP	ITA	0,1		RESP	
OELV	IRL	0,1		RESP	
VL	LUX	0,1		RESP En Silica	
RD	LTU	0,1			
TLV	MLT	0,1		RESP As Silica	
TLV	NOR	0,1		RESP	
TGG	NLD	0,075		RESP	
VLE	PRT	0,025		RESP	
NDS/NDSch	POL	0,1		RESP	
TLV	ROU	0,1		RESP	
NGV/KGV	SWE	0,1		RESP	
NPEL	SVK	0,1		RESP	
MV	SVN	0,15		RESP	
OEL	EU	0,1		RESP	
TLV-ACGIH		0,025		RESP	
Free crystalline silica (Fine fraction)					
Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
MAK	AUS	0,05		RESP	
VLEP	BEL	0,025			
TLV	DNK	0,3			
VLA	ESP	0,05		RESP	
TLV	EST	0,1			
VLEP	FRA	0,1		RESP	
GVI/KGVI	HRV	0,1			
VLEP	ITA	0,1		RESP	
OELV	IRL	0,1		RESP	
VL	LUX	0,1		RESP En Silica	
RD	LTU	0,1			
TLV	MLT	0,1		RESP As Silica	
TLV	NOR	0,1		RESP	
TGG	NLD	0,075		RESP	
VLE	PRT	0,025		RESP	
NDS/NDSch	POL	0,1		RESP	
TLV	ROU	0,1		RESP	
NGV/KGV	SWE	0,1		RESP	
NPEL	SVK	0,1		RESP	

		IMPER ITALIA SRL				Revision nr. 1			
		FLASHING DETAILS				Dated 14/11/2024			
						First compilation			
						Printed on 03/12/2024			
						Page n. 9/19			
MV	SVN	0,15				RESP			
OEL	EU	0,1				RESP			
TLV-ACGIH		0,025				RESP			
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
MAK	AUS	0,05							
MAK	CHE	0,2		0,4		INHAL			
VME/VLE	CHE	0,2		0,4		INHAL			
MAK	DEU	0,2		0,4		INHAL			
Predicted no-effect concentration - PNEC									
Normal value in fresh water				0,00339		mg/l			
Normal value in marine water				0,0039		mg/l			
Normal value for fresh water sediment				0,027		mg/kg/d			
Normal value for marine water sediment				0,027		mg/kg/d			
Normal value for water, intermittent release				0,0039		mg/l			
Normal value of STP microorganisms				0,23		mg/l			
Normal value for the terrestrial compartment				0,01		mg/kg/d			
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers			Effects on workers				
Route of exposure		Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			0,11 mg/kg bw/d		0,09 mg/kg bw/d			0,02	
Inhalation		0,04 mg/m3		0,02 mg/m3		0,04 mg/m3		0,02 mg/m3	
Legend:									
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.									
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.									
8.2. Exposure controls									
As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.									
HAND PROTECTION									
Protect hands with category III work gloves.									
The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.									
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.									
SKIN PROTECTION									
Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap									

	IMPER ITALIA SRL	Revision nr. 1 Dated 14/11/2024 First compilation
	FLASHING DETAILS	Printed on 03/12/2024 Page n. 10/19

and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	as showed in color folder	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not flammable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	not available	
Solubility	soluble	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available



FLASHING DETAILS

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	40,52 %		
VOC (Directive 2004/42/EC) :	< 0.01 %	-	< 0.01 g/litre
VOC (volatile carbon)	< 0.01 %	-	< 0.01 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

	IMPER ITALIA SRL	Revision nr. 1 Dated 14/11/2024 First compilation
	FLASHING DETAILS	Printed on 03/12/2024 Page n. 12/19
<u>Interactive effects</u>		
Information not available		
<u>ACUTE TOXICITY</u>		
ATE (Inhalation) of the mixture:		Not classified (no significant component)
ATE (Oral) of the mixture:		Not classified (no significant component)
ATE (Dermal) of the mixture:		Not classified (no significant component)
TALC		
LC50 (Inhalation mists/powders):		> 2,1 mg/l/4h Rat
1,2-BENZISOTHIAZOLIN-3-ONE		
LD50 (Dermal):		> 2000 mg/kg Rat
LD50 (Oral):		450 mg/kg Rat
LC50 (Inhalation mists/powders):		0,21 mg/l/4h
QUARTZ		
LD50 (Dermal):		2000 mg/kg Rat
LD50 (Oral):		> 2000 mg/kg Rat
Free crystalline silica (Fine fraction)		
LD50 (Dermal):		2000 mg/kg Rat
LD50 (Oral):		> 2000 mg/kg Rat
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)		
LD50 (Dermal):		87,12 mg/kg Rabbit
LD50 (Oral):		457 mg/kg Rat
LC50 (Inhalation mists/powders):		0,171 mg/l/4h Rat
<u>SKIN CORROSION / IRRITATION</u>		
Does not meet the classification criteria for this hazard class		
<u>SERIOUS EYE DAMAGE / IRRITATION</u>		
Does not meet the classification criteria for this hazard class		
<u>RESPIRATORY OR SKIN SENSITISATION</u>		
May produce an allergic reaction.		
Contains:		
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)		
1,2-BENZISOTHIAZOLIN-3-ONE		
<u>GERM CELL MUTAGENICITY</u>		
Does not meet the classification criteria for this hazard class		
<u>CARCINOGENICITY</u>		
Does not meet the classification criteria for this hazard class		
TALC		
Overall IARC evaluation: Perineal use of talc-based body powder is possibly carcinogenic to humans (Group2B). Inhaled talc not containing asbestos or asbestiform fibres is not classifiable as to its carcinogenicity (Group 3).		
<u>REPRODUCTIVE TOXICITY</u>		



FLASHING DETAILS

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1,2-BENZISOTHIAZOLIN-3-ONE

LC50 - for Fish	2,15 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	2,9 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,11 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Algae / Aquatic Plants	0,0403 mg/l Pseudokirchneriella subcapitata

QUARTZ

LC50 - for Fish	1000 mg/l/96h
EC50 - for Crustacea	100 mg/l/48h
EC50 - for Algae / Aquatic Plants	100 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	5600 mg/l

Free crystalline silica (Fine fraction)

LC50 - for Fish	1000 mg/l/96h
EC50 - for Crustacea	100 mg/l/48h
EC50 - for Algae / Aquatic Plants	100 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	5600 mg/l

REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LC50 - for Fish	0,19 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	0,16 mg/l/48h Daphnia magna

FLASHING DETAILS

EC50 - for Algae / Aquatic Plants	0,0052 mg/l/72h Skeletonema costatum
Chronic NOEC for Fish	0,02 mg/l Danio rerio
Chronic NOEC for Crustacea	0,1 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	0,00049 mg/l Skeletonema costatum

12.2. Persistence and degradability

TALC	
Solubility in water	< 0,1 mg/l
1,2-BENZISOTHIAZOLIN-3-ONE	
Solubility in water	1288 mg/l
Rapidly degradable	
REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	
Solubility in water	> 10000 mg/l
NOT rapidly degradable	

12.3. Bioaccumulative potential

1,2-BENZISOTHIAZOLIN-3-ONE	
Partition coefficient: n-octanol/water	0,7
BCF	6,62
REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	
Partition coefficient: n-octanol/water	0,75
BCF	< 54

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

	IMPER ITALIA SRL	Revision nr. 1 Dated 14/11/2024 First compilation
	FLASHING DETAILS	Printed on 03/12/2024 Page n. 15/19

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Contained substance

Point	75	1,2-BENZISOTHIAZOLIN-3-ONE
Point	75	REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) REACH Reg.: 01-2120764691-48-XXXX

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

Exterior walls of mineral substrate.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%

	IMPER ITALIA SRL	Revision nr. 1
	FLASHING DETAILS	Dated 14/11/2024 First compilation Printed on 03/12/2024 Page n. 18/19

- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
 23. Delegated Regulation (UE) 2023/707
 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety

	IMPER ITALIA SRL	Revision nr. 1 Dated 14/11/2024 First compilation
	FLASHING DETAILS	Printed on 03/12/2024 Page n. 19/19

laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.