

Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: NEROBIT PRO

· Article number: ZNPR01-05-10-20-21

· **UFI:** 35C1-F0A3-M00U-F0EQ

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Life cycle stages

C Consumer use

PW Widespread use by professional workers

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC10 Roller application or brushing

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Environmental release category

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

· Uses advised against Non-ventilated environments

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Imper Italia srl Via Rita Atria, 9 10079 MAPPANO (TO) Italia tel. +39 011 2225499

fax +39 011 2625187

· Further information obtainable from: safety@imper.it

· 1.4 Emergency telephone number:

National Poisons Information Service (NPIS) - Email:

director.birmingham.unit@npis.org

Members of the public seeking specific information on poisons should contact:

England and Wales: NHS 111 - dial 111;

Scotland: NHS 24 - dial 111;

N Ireland: Contact your local GP or pharmacist during normal hours; click here

(www.gpoutofhours .hscni.net/) for GP services Out-of-Hours;

Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated

exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

toluene

n-butyl acetate

Solvent naphtha (petroleum), light arom.

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

According to the available data, the product does not contain PBT or vPvB substances in a proportion ≥ 0.1 %.

· **PBT**: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties

78-93-3 butanone

List II



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Dangerous components:		
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 Reg.nr.: 01-2119471310-51- XXXX	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	10-15%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32- XXXX	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35- XXXX	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	5-10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29- XXXX	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	2.5-5%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5-5%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≤2.5%
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32- XXXX	styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤2.5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35- XXXX	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	≤2.5%



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

		(Contd. of page 3)
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43- XXXX	butanone Stort SE 3, H336, EUH066	≤2.5%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0 Reg.nr.: 01-2119480412-44- XXXX	n-hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373:C ≥ 5 %	≥0.25-<2.5%
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2 Reg.nr.: 01-2119475515-33- XXXX	heptane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥0.25-<2.5%
CAS: 61791-39-7 EINECS: 263-171-2 Reg.nr.: 01-2119931039-40- XXXX	1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs. Skin Corr. 1C, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≥0.025-<0.25%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

(Contd. on page 5)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 4)

5.3 Advice for firefighters

• **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Protect against electrostatic charges.

Keep respiratory protective device available.

Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide solvent resistant, sealed floor.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

•	Ingredients	with lim	it values	that requi	re monito	ring at the	workplace:
	400 00 0 1						

108-88-3 toluene

IOELV Short-term value: 384 mg/m³, 100 ppm

Long-term value: 192 mg/m³, 50 ppm

Skin

1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

(Contd. on page 6)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

	(Contd. of pa
123-86-4 n-butyl acetate	
IOELV Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm	
141-78-6 ethyl acetate	
IOELV Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm	
67-64-1 acetone	
IOELV Long-term value: 1210 mg/m³, 500 ppm	
100-41-4 ethylbenzene	
IOELV Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin	
78-93-3 butanone	
IOELV Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm	
110-54-3 n-hexane	
IOELV Long-term value: 72 mg/m³, 20 ppm	
142-82-5 heptane	
IOELV Long-term value: 2085 mg/m³, 500 ppm	
DNELs	
108-88-3 toluene	
Oral DNEL 8.13 mg/kg/day (worker)	
Dermal DNEL 384 mg/kg/day (worker)	
Inhalative DNEL 192 mg/m3 (worker)	
1330-20-7 xylene	
Oral DNEL 12.5 mg/kg/day (worker)	
Dermal DNEL 212 mg/kg/day (worker)	
Inhalative DNEL 221 mg/m3 (worker)	
Solvent naphtha (petroleum), light arom.	
Oral DNEL 25 mg/kg/day (worker)	
Inhalative DNEL 150 mg/m3 (worker)	
141-78-6 ethyl acetate	
Inhalative DNEL 734 mg/m3 (worker)	
67-64-1 acetone	
Dermal DNEL 186 mg/kg/day (worker)	
Inhalative DNEL 1,210 mg/m3 (worker)	
78-93-3 butanone	
Dermal DNEL 1,161 mg/kg/day (worker)	
142-82-5 heptane	
Dermal DNEL 300 mg/kg/day (worker)	
Inhalative DNEL 2,085 mg/m3 (worker)	
PNECs	
1330-20-7 xylene	
PNEC 0.32 mg/l	
141-78-6 ethyl acetate	
PNEC 0.24 mg/l	



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 6)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data: see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

- · Body protection: Protective work clothing
- · Skin protection

Wear long-sleeved work clothes and safety footwear for professional use (ref. Regulation 2016/425 and EN ISO 20344). Wash with soap and water after removing protective clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid
Black
Aromatic
Not determined.
Undetermined.

· Boiling point or initial boiling point and

boiling range 110-111 °C (108-88-3 toluene)

· **Flammability** Highly flammable.

· Lower and upper explosion limit

• **Lower:** 1.2 Vol % (108-88-3 toluene) • **Upper:** 7 Vol % (108-88-3 toluene)

(Contd. on page 8)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 7)

· Flash point: -19 °C

• Auto-ignition temperature: >450 °C (1330-20-7 xylene)

• **Decomposition temperature:** Not determined.

pH Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 29 hPa (108-88-3 toluene)

• Vapour pressure at 50 °C: 124 hPa

Density and/or relative density

• **Density at 20 °C:** 0.92-1 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

· VOC (EC) 380-400 g/l

40.74 %

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability No further relevant information available.

(Contd. on page 9)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 8)

- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

		evant for classification:
ATE (Acu	te Toxicity	y Estimates)
Dermal	LD50	28,289 mg/kg (rabbit)
Inhalative	LC50/4 h	130 mg/l
108-88-3	toluene	
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
1330-20-7	xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
		etroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
123-86-4	n-butyl ac	etate
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
141-78-6	ethyl aceta	ate
Oral	LD50	4,934 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
100-42-5	styrene	
Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)
	ethylbenz	
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
78-93-3 b	utanone	
Oral	LD50	2,737 mg/kg (rat)
Dermal	LD50	6,480 mg/kg (rabbit)
		23.5 mg/l (rat)
61791-39-		azole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs.
Oral	LD50	947 mg/kg (rat)

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 10)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 9)

- · Reproductive toxicity Suspected of damaging the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure

May cause damage to the hearing organs through prolonged or repeated exposure.

- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards
- Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

The classification in the European waste catalogue must be done for the branch and the process type.

- Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

UN1263

(Contd. on page 11)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 10) · 14.2 UN proper shipping name · ADR, IMDG, IATA **PAINT** · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E Stowage Category · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 5L Code: E2 Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml **UN "Model Regulation":** UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2004/42/EC

Product type: PAINTS AND VARNISHES
• Product subcategory: Binding primers

· Solvent-borne coatings, Limit value: 750 g/l

VOC: 380-400 g/l

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 12)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 11)

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation	Regulation (EC) No 273/2004 on drug precursors		
108-88-3	toluene	3	
67-64-1	acetone	3	
78-93-3	butanone	3	

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

	· ·	- 1	
108-88-3	toluene	3	
67-64-1	acetone	3	
78-93-3	butanone	3	

· National regulations:

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H225	Highly flan	nmable liquid	and vapour.

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 13)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

Classification according to Regulation (EC) N	
Flammable liquids	Bridging principles
Skin corrosion/irritation	The classification of the mixture is generall
Serious eye damage/irritation	based on the calculation method usin
Reproductive toxicity	substance data according to Regulation (EC) N
Specific target organ toxicity (single exposure)	1272/2008.
Specific target organ toxicity (repeated exposure	
Hazardous to the aquatic environment - long-	
term (chronic) aquatic hazard	
(
Aspiration hazard	Expert judgement

· Date of previous version: 12.12.2022 · Version number of previous version: 1

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 2: Reproductive toxicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

Annex: Exposure scenario

- · Short title of the exposure scenario
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC10 Roller application or brushing

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

(Contd. on page 14)



Printing date 23.02.2024 Version number 2 (replaces version 1) Revision: 05.02.2024

Trade name: NEROBIT PRO

(Contd. of page 13)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity According to directions for use.
- Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting worker exposure

Outdoor application.

Avoid contact with eyes.

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures

No special measures required.

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

No special measures required.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Pregnant women should strictly avoid inhalation or skin contact.

Tightly sealed goggles

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

No special measures required.

Ensure adequate labelling.

Environmental protection measures

- · Air No special measures required.
- · Water No special measures required.
- Disposal measures Ensure that waste is collected and contained.

· Disposal procedures

Dispose of product residues with household waste.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.